



LOW PRESSURE AIR CONTROL SYSTEMS

In-Line Air Filters and Air Filter/Regulator Systems



Model Number
234410



Model Number
234399



Model Number
234400

Air filters and regulators for low-pressure applications

FEATURES

- Remove contaminants down to 5 microns
- Perfect point-of-use filters for air-operated equipment
- Specifically designed for low pressure applications
- Systems with up to two air controls for multiple drops
- Reusable edge-type filter element design
- Auto-drain valves on in-line filter and coalescer

BENEFITS

- Dry air for all air-operated equipment
- Clean and dry air increases equipment life and product performance
- Easy to install in your existing compressed air system
- Reduce total number of filters required and lower costs
- Lower total cost of ownership
- Eliminate manual emptying of filters

INDUSTRIAL

PROVEN QUALITY. LEADING TECHNOLOGY.

Technical Specifications & Ordering Information

Air Control Systems

Part Number	Description	Max. Air Inlet Pressure	Weight	Max. CFM
234398	Air control unit, filtered main air outlet, two regulated outlets	160 psi (1.1 MPa, 11 bar)	5 lb 12 oz (2.6 kg)	120 CFM – Filter 50 CFM – Air Regulator
234399	Air control unit, filtered main air outlet with gauge, two regulated outlets	160 psi (1.1 MPa, 11 bar)	6 lb 4 oz (2.8 kg)	120 CFM – Filter 50 CFM – Air Regulator
234400	Air control unit, filtered main air outlet with gauge, three regulated outlets	160 psi (1.1 MPa, 11 bar)	7 lb 13 oz (3.5 kg)	120 CFM – Filter 50 CFM – Air Regulator
234411	Air control unit, filtered main air outlet, two regulated outlets	160 psi (1.1 MPa, 11 bar)	4 lb 13 oz (2.2 kg)	75 CFM – Filter 50 CFM – Air Regulator

Air Filters

Part Number	Description	Inlet	Outlet	Max. Air Inlet Pressure	Weight	Max. CFM
234396	Air filter, bare	1/2" npt (f)	3/8" npt (f)	175 psi (1.2 MPa, 12 bar)	3 lb 10 oz (1.6 kg)	120 CFM
234410	Air filter, bare	1/2" npt (f)	3/8" npt (f) 1/4" npt (f) plugged	175 psi (1.2 MPa, 12 bar)	2 lb 11 oz (1.2 kg)	75 CFM
234412	Air filter, quick coupler	1/4" npt (f)	1/4" npt (f) 1/4" npt (f) plugged	175 psi (1.2 MPa, 12 bar)	3 lb 2 oz (1.4 kg)	75 CFM

Instruction Manual

309923

All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Call today for product information or to request a demonstration.

1.877.84GRACO (1-877-844-7226) or visit us at www.graco.com.

